



DIMENSIONAL TOLERANCE TABLE	
TOLERANCE	DIVISION
Less than 4.0	±0.3
4.0~16.0	±0.5
16.0~63.0	±0.7
63.0~250.0	±1.2
250.0~1000.0	±2.0

SCALE : mm

\*2

\*1: SPCC, etc (COVER PART, COLOR: IVORY)

RoHS Compliant $Cd \leq 75ppm$	
REMARKS	BRASS: $Cd \leq 75ppm$ PHOSPHOR BRONZE: $Pb < 4wt\%$

7						SCALE	1/1	DRAWN	INSPECTED	APPROVED	CHECKED	PART NUMBER
6						TOLERANCE	*2	井	檜	山	三	BNC-0094
5						UNIT	mm	'24.04.11	'24.04.11	'24.04.11	'24.04.11	
4								出	澤	本	村	
3												
2	LABEL	-----	1	--								
1	BNC-J TYPE COAXIAL 4 DISTRIBUTOR	*1	1	--	BODY/Ni, CENTER PIN/Aq	DATE	2024.04.11	PROJECTION				DRAWING NO. U-0396557
NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH	REMARK							

# PRODUCT SPECIFICATIONS

Part number: BNC-0094

No. 0392672

Drawing number: U-0396557

Nominal	1 Standard	JIS C 5412
	2 Power handling	250mW
	3 Rated frequency	40MHz~900MHz
	4 Impedance	50Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C, 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C, 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks	
1	E L E C T R I C A L	Frequency characteristic	40MHz~900MHz: 2.0dB(Max.)	
2		Isolation	40MHz~900MHz: 20dB(Min.)	
3		VSWR	40MHz~900MHz: 1.5(Max.)	
4		Insertion loss	40MHz~900MHz: 8.0dB(Max.)	
5	M E C H A N I C A L  O T H E R S	Compatibility	No defects or abnormalities	Connecting with a standard-compliant connector

※The structural shape is shown in the attached drawing (Drawing number:U-0396557)

	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
 三 24.04.11 村	 山 24.04.11 本	 檜 24.04.11 澤	 井 24.04.11 出

GKQM-24