



DIMENSIONAL TOLERANCE TABLE	
TOLERANCE	DIVISION
Less than 4.0	±0.3
4.0~16.0	±0.5
16.0~63.0	±0.7
63.0~250.0	±1.2
250.0~1000.0	±2.0

SCALE : mm
*2

*1: SPCC, etc (COVER PART, COLOR: IVORY)

RoHS Compliant [Cd ≤75ppm]	
REMARKS	BRASS: Cd ≤75ppm PHOSPHOR BRONZE: Pb <4wt%

7						SCALE	DRAWN	INSPECTED	APPROVED	CHECKED	PART NUMBER
6						2/3	井	檜	山	三	
5						TOLERANCE	'24.04.16	'24.04.16	'24.04.16	'24.04.16	
4						*2	出	澤	本	村	
3						UNIT	PROJECTION				DRAWING NO. U-0596563
2	LABEL	-----	1	--		mm					
1	N-J TYPE COAXIAL 4 DISTRIBUTOR	*1	1	--	BODY/Ni, CENTER PIN/Aq	DATE					
NO.	DESCRIPTION	MATERIAL	Q'TY	FINISH	REMARK	2024.04.16					

PRODUCT SPECIFICATIONS

Part number: N-0094

No. 0592677

Drawing number: U-0596563

Nominal	1 Standard	JIS C 5411
	2 Power handling	250mW
	3 Rated frequency	40MHz~900MHz
	4 Impedance	50Ω(unbalance)
	5 Operating temperature and humidity range	0°C~+50°C、 30~90%RH※No condensation
	6 Storage temperature and humidity range	-20°C~+70°C、 30~90%RH ※No condensation



	Test Items	Test Method/Value	Remarks	
1	E L E C T R I C A L	Frequency characteristic	40MHz~900MHz: 2.0dB(Max.)	
2		Isolation	40MHz~900MHz: 20dB(Min.)	
3		VSWR	40MHz~900MHz: 1.5(Max.)	
4		Insertion loss	40MHz~900MHz: 8.0dB(Max.)	
5	M E C H A N I C A L O T H E R S	Compatibility	No defects or abnormalities	
				Connecting with a standard-compliant connector

※The structural shape is shown in the attached drawing (Drawing number:U-0596563)

	REVISIONS	DATE
1		
2		
3		

Checked	Approved	Inspected	Prepared
24.04.16	24.04.16	24.04.16	24.04.16
村	本	澤	出

GKQM-24