

3.5mm connector **3.5-A-PP**

50Ω Adapter

New Product Stock RoHS2



Description

The 3.5-A-PP is a 3.5mm Adapter connector. This connector is suitable for various high-frequency applications. It features a impedance 50Ω, operates up to 26.5GHz, and has a rated voltage of AC 335V, ensures a high insulation resistance (5000MΩ (Min.) at DC 500V), a low contact resistance (Between inner conductors: 3 mΩ (Max.), between outer conductors: 2.5 mΩ (Max.), and an excellent V.S.W.R 1.2 (Max.) at DC~26.5GHz. The contact is made of Beryllium Copper/Gold Plating, while the body is Stainless/Passivate Treatment. We can customize our products for you. We offer total customization, including changes to a product's shape, length, material, surface treatment, and packaging. Being registered with Square and Paypal allows us to accept credit card payments from various brands. Available from 1 piece for in-stock items.

Specifications

Connector Gender	Plug Plug
Impedance (Ohms)	50Ω
Rated Voltage AC	AC 335V
Operating Frequency Range	26.5GHz
Insulation Resistance	5000MΩ (Min.) at DC 500V
Withstand Voltage	AC 1000V(1 minute)
Contact Resistance	Between inner conductors: 3 mΩ (Max.), between outer conductors: 2.5 mΩ (Max.)
V.S.W.R	1.2(Max.) at DC~26.5GHz

Material/Plating/Attachment

Contact	Beryllium Copper/Gold Plating
Body	Stainless/Passivate Treatment

<https://www.to-conne.co.jp/en.html>

TO-CONNE CO., LTD

【Address】 5-23-11 Narimasu, Itabashi-ku
Tokyo 175-0094, Japan

TEL (+81) 3-3939-9161

MAIL overseas@to-conne.co.jp

