

In/Between Series Adaptors **BNC-TA-JPJ-K**



50Ω Adapter

Stock RoHS2

Description

The BNC-TA-JPJ-K is an In/Between Series Adaptors . This connector is suitable for various high-frequency applications. It features a impedance 50Ω, operates up to 3GHz, and has a rated voltage of AC 500V, ensures a high insulation resistance (1000MΩ (Min.) at DC 500V), a low contact resistance (3 mΩ (Max.)), and an excellent V.S.W.R 1.2(Max.) at DC~200MHz. Withstanding temperatures from -40 to +85°C. The contact is made of Brass/Gold Plating, while the body is Brass/Zinc Die Casting/Nickel Plating. We can customize our products for you. We offer total customization, including changes to a product's shape, length, material, surface treatment, and packaging. Being registered with Square and Paypal allows us to accept credit card payments from various brands. Additionally, this connector is available for purchase on Digi-Key. Available from 1 piece for in-stock items.

Specifications

| | |
|-----------------------------|--------------------------|
| Connector Gender | Jack Plug Jack |
| Impedance (Ohms) | 50Ω |
| Rated Voltage AC | AC 500V |
| Operating Frequency Range | 3GHz |
| Insulation Resistance | 1000MΩ (Min.) at DC 500V |
| Withstand Voltage | AC 1500V(1 minute) |
| Contact Resistance | 3 mΩ (Max.) |
| V.S.W.R | 1.2(Max.) at DC~200MHz |
| Operating Temperature Range | -40 to +85°C |

Material/Plating/Attachment

| | |
|---------|---------------------------------------|
| Contact | Brass/Gold Plating |
| Body | Brass/Zinc Die Casting/Nickel Plating |

<https://www.to-conne.co.jp/en.html>

TO-CONNE CO., LTD

【Address】 5-23-11 Narimasu, Itabashi-ku
Tokyo 175-0094, Japan

TEL (+81) 3-3939-9161

MAIL overseas@to-conne.co.jp

